

Pole Puller



Specifications:

	PP-30-HD	PP-60-XHD
<i>Performance:</i>	Pull (lb.) at 2,500 psi 60,000	Pull (lb.) at 2,250 psi 125,000
<i>Maximum Pole Size:</i>	18" Diameter 56" Circumference	26" Diameter 81" Circumference
<i>Cylinder:</i>	Stroke 24" Bore 4" Rod 3"	Stroke 24" Bore 6" Rod 4"
<i>Head:</i>	Cam action head has beveled teeth to provide a better grip. Chain-(2) 1/2" x 5' long on the drum head	Cam action head has beveled teeth to provide a better grip. Chain-(2) 3/4" x 4" x 5' long on the drum head
<i>Base Weldment:</i>	Exterior 32" x 32" Interior 20" x 26" Weight 700 lbs.	Exterior 46" x 46" Interior 28" x 28" Weight 1,500 lbs.
<i>Lifting Points:</i>	2 lifting eyes on the head Forklift pockets - 2 1/2" x 5 1/2" x 32" long	2 chains on the head Forklift pockets - 3.25" x 7.25" x 46" long

Common Specifications:

Controls:

- Utilize controls on power source (skid steer, crane or derrick)

Hydraulics:

- Required flow rate 5-15 gpm @ 2,500 psi
- Storage of hoses on the base (2) 25 ft. long

DIVERSIFIED

P R O D U C T S

1001 Webster Avenue
Waco, Texas 76706
254-757-1177 phone
noahg@diversifiedproduct.com
www.diversifiedproduct.com

© 2010 Diversified Products